



Perforated cable tray



Available in heights (H):

15

| Dimension | | | Thickness | Th (18-42) | Weight (01) | Weigh (18-42) | Length | Code | | | | |
|-----------|----|----|-----------|------------|-------------|---------------|--------|------|------|------|------|-------------|
| W (B) | | | [mm] | [mm] | [Kg/m] | [Kg/m] | [mm] | | | | | |
| 50 | 01 | 03 | 17 | 18 | 41 | 42 | 1,50 | 2,00 | 0,81 | 0,36 | 2000 | NA 002 0105 |
| 75 | 01 | 03 | 17 | 18 | 41 | 42 | 1,50 | 2,00 | 1,06 | 0,48 | 2000 | NA 002 0107 |
| 100 | 01 | 03 | 17 | 18 | 41 | 42 | 1,50 | 2,00 | 1,32 | 0,59 | 2000 | NA 002 0110 |
| 125 | 01 | 03 | 17 | 18 | 41 | 42 | 1,50 | 2,00 | 1,57 | 0,71 | 2000 | NA 002 0112 |
| 150 | 01 | 03 | 17 | 18 | 41 | 42 | 1,50 | 2,00 | 1,83 | 0,82 | 2000 | NA 002 0115 |
| 200 | 01 | 03 | 17 | 18 | 41 | 42 | 1,50 | 2,00 | 2,34 | 1,06 | 2000 | NA 002 0120 |
| 250 | 01 | 03 | 17 | 18 | 41 | 42 | 1,50 | 2,00 | 2,85 | 1,29 | 2000 | NA 002 0125 |
| 300 | 01 | 03 | 17 | 18 | 41 | 42 | 1,50 | 2,00 | 3,36 | 1,52 | 2000 | NA 002 0130 |
| 400 | 01 | 03 | 17 | 18 | 41 | 42 | 1,50 | 2,00 | 4,38 | 1,98 | 2000 | NA 002 0140 |

List of Coatings

- Galvanization (Sendzimir method) - UNI EN 10346
- Hot dip galvanizing - UNI EN ISO 1461
- Send Galvanizing + White Ral 9010
- Aluminium + White Ral 9010
- Stainless steel AISI 316L - UNI EN 10088
- ENAW 1050H24 - Aluminium