



Cable ladder



Available in heights (H):

45

Dimension	 Technical Info				Coatings 25-03-41	Coating 25	Coating 42		Code
W (B)	L [mm]	Thickness [mm]	Weigh [Kg/m]	Thickness [mm]	Weigh [Kg/m]	Thickness [mm]	Weigh [Kg/m]		
150	03 25 41 42	3000	1,50	1,95	2,00	0,87	NT 003 0415		
200	03 25 41 42	3000	1,50	2,08	2,00	0,93	NT 003 0420		
250	03 25 41 42	3000	1,50	2,21	2,00	0,98	NT 003 0425		
300	03 25 41 42	3000	1,50	2,33	2,00	1,04	NT 003 0430		
350	03 25 41 42	3000	1,50	2,46	2,00	1,09	NT 003 0435		
400	03 25 41 42	3000	1,50	2,58	2,00	1,15	NT 003 0440		
450	03 25 41 42	3000	1,50	2,71	2,00	1,21	NT 003 0445		
500	03 25 41 42	3000	1,50	2,83	2,00	1,26	NT 003 0450		
550	03 25 41 42	3000	1,50	2,96	2,00	1,32	NT 003 0455		
600	03 25 41 42	3000	1,50	3,09	2,00	1,38	NT 003 0460		

List of Coatings

- Hot dip galvanizing - UNI EN ISO 1461
- Electro galvanization - DIN 50962
- Stainless steel AISI 316L - UNI EN 10088
- ENAW 1050H24 - Aluminium

Cable ladder

Assembly

