Basket Tray

For naval applications:
- H.30 - from B.100 to B.300
- H.60 - from B.100 to B.500

H.30 - Not UL certified





RV 003 0610

Length: 3000

Coatings

- 03 Hot dip galvanizing - UNI EN ISO 1461
- 25 Electrogalvanization - DIN 50962
- 40 Stainless steel AISI 304 - UNI EN 10088

Technical Characteristics	
Dimension	
W (B)	100
Weight	
[Kg/m]	0,76
L	
[mm]	3000
Technical Info	
Clip on base*	–
H [mm]	60
W [mm]	102
SWL [N/m 1,5m]	323
n° wires	2
Wire Ø	
03	3,90
25	3,90
40	4,00
UL Certification	
UL suffix	UL

* To request UL certified material add the suffix UL to the code - Ex: **RV 003 0606 25 UL**

* Quick joint clip on trays base Absent (-)
* Quick joint clip on trays base Present (n)

Zamet S.p.A.
Via Torino, 109 - 10088 Volpiano (TO) - Italy
Tel. +39(011)98.22.601 - www.zamet.it

Basket Tray

Rod pitch (mesh width): 50 mm (on the base B)

**** Usable sections see Assembly page (download Documents)***

RV 013 - wires version (2 wires on the base)

1) Hot dip galvanized
2) Stainless Steel AISI 304 / AISI 316L
1) Classified 8 – according to IEC 61537 Average Thickness of Zinc layer for HDG coatings ranges from 85 µm to 100 µm 2) Classified 9D – according to IEC 61537 corrosion resistance

Certifications

Basket Tray

Load Diagram



y= Max load (N/m)
x= Distance between supports (m)

Zamet S.p.A.
Via Torino, 109 - 10088 Volpiano (TO) - Italy
Tel. +39(011)98.22.601 - www.zamet.it