



Central Reducer with Cover

The product with code T00711514, described as CENTRAL REDUCTION COP 50X200/50X 150, belongs to the category of cable duct components. This reducer is designed with a safety profile and snap-on cover and is intended to facilitate the transition between ducts of different sizes with a height of 50 mm. Its robust structure and precision construction ensure optimal adaptation from 200 mm to 150 mm. Made of 1.0 mm thick Sendzimir galvanised steel and 0.8 mm thick for the cover, it is also available in hot-dip galvanised, painted and stainless steel finishes. This product is an efficient and practical solution for those looking for a cable duct reducer that combines quality, functionality and ease of installation.



T0 071 1514

Length: 0

Coatings

- 01 Galvanization (Sendzimir method) - UNI EN 10346
- 03 Hot dip galvanizing - UNI EN ISO 1461
- 11 Grey RAL 7032 - ISO9227-ISO6270-ISO2810
- 15 Blue RAL 5015 - ISO9227-ISO6270-ISO2810
- 40 Stainless steel AISI 304 - UNI EN 10088
- 41 Stainless steel AISI 316L - UNI EN 10088

Technical Characteristics	
Weight	
[Kg]	0.83
Technical Info	
L	220
Reduction from	
W (B)	200
W1 (B1)	150

Certified System
- IMQ
- EN 61537-1 ed.2007
- EN 50085-1:2005 ed EN 50085-2-1:2006
- UL file E471266
Attention: for ZT and ZM material sold/assembled in U.S.A. and Canada, please require UL mark

Thickness

T1 071 - Component - 1,00mm
T1 072 - Cover - 0,80mm

Certifications

