



Central Reducer with Cover

The product with code T00712726, described as CENTRAL REDUCTION COP 75X 400/75X 300, belongs to the category of cable duct components. This reducer is designed with a safety profile and snap-on cover and is intended to facilitate the transition between ducts of different sizes with a height of 75 mm. Its sturdy structure and precision construction ensure optimal adaptation from 400 mm to 300 mm. Made of 1.0 mm thick Sendzimir galvanized steel and 0.8 mm thick for the cover, it is also available in hot-dip galvanized, painted, and stainless steel finishes. This product is an efficient and practical solution for those looking for a cable duct reducer that combines quality, functionality, and ease of installation.



T0 071 2726

Length: 0

Coatings

- 01 Galvanization (Sendzimir method) - UNI EN 10346
- 03 Hot dip galvanizing - UNI EN ISO 1461
- 11 Grey RAL 7032 - ISO9227-ISO6270-ISO2810
- 15 Blue RAL 5015 - ISO9227-ISO6270-ISO2810
- 40 Stainless steel AISI 304 - UNI EN 10088
- 41 Stainless steel AISI 316L - UNI EN 10088

Technical Characteristics

Weight

[Kg] 1.45

Technical Info

L 220

Reduction from

W (B) 400

W1 (B1) 300

Certified System

- IMQ
 - EN 61537-1 ed.2007
 - EN 50085-1:2005 ed EN 50085-2-1:2006
 - UL file E471266
- Attention: for ZT and ZM material sold/assembled in U.S.A. and Canada, please require UL mark

Certifications



Thickness

T1 071 - Component - 1,00mm

T1 072 - Cover - 0,80mm