


Height Reducer with Cover



Available in heights (H):

75-50 00-75

| Dimension | | | | | Weight | Code |
|-----------|------|----|----|----|--------|-------------|
| W (B) | [Kg] | | | | | |
| 100 | 01 | 11 | 15 | 40 | 0,11 | T0 079 3323 |
| 150 | 01 | 11 | 15 | 40 | 0,15 | T0 079 3424 |
| 200 | 01 | 11 | 15 | 40 | 0,18 | T0 079 3525 |
| 300 | 01 | 11 | 15 | 40 | 0,23 | T0 079 3626 |
| 400 | 01 | 11 | 15 | 40 | 0,29 | T0 079 3727 |
| 500 | 01 | 11 | 15 | 40 | 0,35 | T0 079 3828 |
| 600 | 01 | 11 | 15 | 40 | 0,40 | T0 079 3929 |

Certifications



List of Coatings

- Galvanization (Sendzimir method) - UNI EN 10346
- Grey RAL 7032 - ISO9227-ISO6270-ISO2810
- Blue RAL 5015 - ISO9227-ISO6270-ISO2810
- Stainless steel AISI 304 - UNI EN 10088

Certified System

- IMQ
- EN 61537-1 ed.2007
- EN 50085-1:2005 ed EN 50085-2-1:2006
- UL file E471266
- Attention: for ZT and ZM material sold/assembled in U.S.A. and Canada, please require UL mark

Height Reducer with Cover

Assembly

