


### 30° flat elbow with Cover



Available in heights (H):

- 50
- 75
- 100

Dimension							Weight	Technical Info			Code
W (B)							[Kg]	a	w (b)	R	
75	01	03	11	15	40	41	0,36	143	102	100	T0 089 0707
100	01	03	11	15	40	41	0,43	156	127	100	T0 089 0710
150	01	03	11	15	40	41	0,58	181	177	100	T0 089 0715
200	01	03	11	15	40	41	0,76	206	227	100	T0 089 0720
300	01	03	11	15	40	41	1,15	256	327	100	T0 089 0730
400	01	03	11	15	40	41	1,60	306	427	100	T0 089 0740
500	01	03	11	15	40	41	2,15	356	527	100	T0 089 0750
600	01	03	11	15	40	41	2,78	406	627	100	T0 089 0760

#### Thickness

T1 089 - Component - 1,00mm

T1 090 - Cover - 0,80mm

#### \*T0 089 0507 - Dimension on demand

#### Certifications



E471266



#### List of Coatings

Galvanization (Sendzimir method) - UNI EN 10346

Hot dip galvanizing - UNI EN ISO 1461

Grey RAL 7032 - ISO9227-ISO6270-ISO2810

Blue RAL 5015 - ISO9227-ISO6270-ISO2810

Stainless steel AISI 304 - UNI EN 10088

Stainless steel AISI 316L - UNI EN 10088

#### Certified System

- IMQ

- EN 61537-1 ed.2007

- EN 50085-1:2005 ed EN 50085-2-1:2006

- UL file E471266

Attention: for ZT and ZM material sold/assembled in U.S.A. and Canada, please require UL mark