


45° Outside Elbow with Cover



Available in heights (H):

50

75

100

Dimension							Weight	Technical Info	Code
W (B)							[Kg]	a w (b) R	
50	01	03	11	15	40	41	0,24	101 157 100	T0 099 0505
100	01	03	11	15	40	41	0,40	101 157 100	T0 099 0510
150	01	03	11	15	40	41	0,35	101 157 100	T0 099 0515
200	01	03	11	15	40	41	0,56	101 157 100	T0 099 0520
300	01	03	11	15	40	41	0,78	101 157 100	T0 099 0530
400	01	03	11	15	40	41	1,09	101 157 100	T0 099 0540
500	01	03	11	15	40	41	1,22	101 157 100	T0 099 0550
600	01	03	11	15	40	41	1,44	101 157 100	T0 099 0560

Thickness

T1 099 - Component - 1,00mm

T1 100 - Cover - 0,80mm

*T0 099 0507 - Dimension on demand

Certifications



E471266



List of Coatings

Galvanization (Sendzimir method) - UNI EN 10346

Hot dip galvanizing - UNI EN ISO 1461

Grey RAL 7032 - ISO9227-ISO6270-ISO2810

Blue RAL 5015 - ISO9227-ISO6270-ISO2810

Stainless steel AISI 304 - UNI EN 10088

Stainless steel AISI 316L - UNI EN 10088

Certified System

- IMQ

- EN 61537-1 ed.2007

- EN 50085-1:2005 ed EN 50085-2-1:2006

- UL file E471266

Attention: for ZT and ZM material sold/assembled in U.S.A. and Canada, please require UL mark