


30° Outside Elbow with Cover

Product T01010707, called 30° Outside Elbow with Cover 75x75, is a component designed for cable routing. Its 30° geometry allows the route to be varied while ensuring the continuity of the channel and compliance with the minimum bending radius. The entire range has an internal radius of 100 mm, in line with the typical requirements of electrical installations and structured cabling systems. The body of the bend is made of 1.0 mm thick Sendzimir galvanised steel, while the cover is 0.8 mm thick. The closure system features a self-locking snap-on cover, designed to ensure quick installation and operational safety thanks to its accident prevention profile. The component is also available in hot-dip galvanised, painted and stainless steel finishes to suit different requirements for mechanical strength, corrosion protection and environmental conditions of installation.



T0 101 0707

Length: 0

Coatings

- | | |
|----|---|
| 01 | Galvanization (Sendzimir method) - UNI EN 10346 |
| 03 | Hot dip galvanizing - UNI EN ISO 1461 |
| 11 | Grey RAL 7032 - ISO9227-ISO6270-ISO2810 |
| 15 | Blue RAL 5015 - ISO9227-ISO6270-ISO2810 |
| 40 | Stainless steel AISI 304 - UNI EN 10088 |
| 41 | Stainless steel AISI 316L - UNI EN 10088 |

Technical Characteristics	
Dimension	
W (B)	75
Weight	
[Kg]	0,34
Technical Info	
a	105
w (b)	144
R	100

Certified System

- IMQ
 - EN 61537-1 ed.2007
 - EN 50085-1:2005 ed EN 50085-2-1:2006
 - UL file E471266
- Attention: for ZT and ZM material sold/assembled in U.S.A. and Canada, please require UL mark

Certifications



E471266



Thickness

T1 101 - Component - 1,00mm

T1 102 - Cover - 0,80mm

***T0 101 0507 - Dimension on demand**