


90° Vertical inside/outside elbow with Cover

Product T01030520, called 90° Vertical inside/outside elbow with Cover 50x200, is a component designed to modify the cable route while ensuring channel continuity and compliance with the minimum bending radius. The entire range has an internal radius of 100 mm, in line with the requirements of electrical installations and structured cabling systems. The body of the bend is made of 1.0 mm thick Sendzimir galvanised steel, while the two covers are 0.8 mm thick. The closure system uses self-locking snap-on covers, designed to offer quick installation, operational safety and protection thanks to the accident prevention profile. The component is also available in hot-dip galvanised, painted and stainless steel versions to suit different requirements for mechanical strength, corrosion protection and environmental installation conditions.



T0 103 0520

Length: 0

Coatings

- 01 Galvanization (Sendzimir method) - UNI EN 10346
- 03 Hot dip galvanizing - UNI EN ISO 1461
- 11 Grey RAL 7032 - ISO9227-ISO6270-ISO2810
- 15 Blue RAL 5015 - ISO9227-ISO6270-ISO2810
- 40 Stainless steel AISI 304 - UNI EN 10088
- 41 Stainless steel AISI 316L - UNI EN 10088

Technical Characteristics

Dimension

W (B) 200

Weight

[Kg] 1,07

Technical Info

a 180

R 100

Certified System

- IMQ
 - EN 61537-1 ed.2007
 - EN 50085-1:2005 ed EN 50085-2-1:2006
 - UL file E471266
- Attention: for ZT and ZM material sold/assembled in U.S.A. and Canada, please require UL mark

Certifications



E471266



Thickness

T1 103 - Component - 1,00mm

T1 104 - Cover - 0,80mm

*T0 103 0507 - Dimension on demand