



Horizontal "T" Junction with Cover

Product T01050505, called Horizontal "T" Junction with Cover 50x50, is a component designed to create a flat deviation with three equal outlets, ensuring channel continuity and compliance with the minimum cable bending radius. The entire range has an internal radius of 100 mm, in line with the requirements of electrical installations and structured cabling systems. The body of the connector is made of 1.0 mm thick Sendzimir galvanised steel, while the cover is 0.8 mm thick. The closure system uses a self-locking snap-on cover, designed to offer quick installation, operational safety and protection thanks to its accident prevention profile. The component is also available in hot-dip galvanised, painted and stainless steel versions to suit different requirements for mechanical strength, corrosion protection and environmental installation conditions.



T0 105 0505

Length: 0

Coatings

- 01 Galvanization (Sendzimir method) - UNI EN 10346
- 03 Hot dip galvanizing - UNI EN ISO 1461
- 11 Grey RAL 7032 - ISO9227-ISO6270-ISO2810
- 15 Blue RAL 5015 - ISO9227-ISO6270-ISO2810
- 40 Stainless steel AISI 304 - UNI EN 10088
- 41 Stainless steel AISI 316L - UNI EN 10088

Technical Characteristics	
Dimension	
W (B)	50
Weight	
[Kg]	0,82
Technical Info	
a	180
w (b)	310
R	100

Certified System
- IMQ
- EN 61537-1 ed.2007
- EN 50085-1:2005 ed EN 50085-2-1:2006
- UL file E471266
Attention: for ZT and ZM material sold/assembled in U.S.A. and Canada, please require UL mark

Certifications

Thickness

T1 105 - Component - 1,00mm

T1 106 - Cover - 0,80mm

***T0 105 0507 - Dimension on demand**

