


Cross with Cover



Available in heights (H):

50

75

100

Dimension							Weight	Technical Info			Code
W (B)	01	03	11	15	40	41	[Kg]	a	R		
100	01	03	11	15	40	41	1,81	360	100	T0 111 1010	
150	01	03	11	15	40	41	2,44	410	100	T0 111 1015	
200	01	03	11	15	40	41	3,05	460	100	T0 111 1020	
300	01	03	11	15	40	41	4,50	560	100	T0 111 1030	
400	01	03	11	15	40	41	6,22	660	100	T0 111 1040	
500	01	03	11	15	40	41	8,25	760	100	T0 111 1050	
600	01	03	11	15	40	41	10,52	860	100	T0 111 1060	

Thickness

T1 111 - Component - 1,00mm

T1 112 - Cover - 0,80mm

***T0 111 0507 - Dimension on demand**

Certifications



E471266



List of Coatings

Galvanization (Sendzimir method) - UNI EN 10346

Hot dip galvanizing - UNI EN ISO 1461

Grey RAL 7032 - ISO9227-ISO6270-ISO2810

Blue RAL 5015 - ISO9227-ISO6270-ISO2810

Stainless steel AISI 304 - UNI EN 10088

Stainless steel AISI 316L - UNI EN 10088

Certified System

- IMQ

- EN 61537-1 ed.2007

- EN 50085-1:2005 ed EN 50085-2-1:2006

- UL file E471266

Attention: for ZT and ZM material sold/assembled in U.S.A. and Canada, please require UL mark