


“T” junction descending with Cover

Product T01130760, called a “T” junction descending with Cover 75x600, consists of a T-shaped element that allows the connection between three sections of duct arranged on two different levels, ensuring orderly, safe routing that complies with current installation regulations. It is particularly suitable for industrial and civil electrical systems that require high flexibility in cable routing. The entire range is manufactured with an internal radius of 100 mm, in line with the requirements of modern electrical systems and structured cabling infrastructures. The body of the component is made of 1.0 mm thick sendzimir galvanised steel, while the cover, equipped with a self-locking snap closure system, is made of 0.8 mm thick steel. This system guarantees quick installation, operational safety and effective protection thanks to its accident prevention profile. The product is also available in hot-dip galvanised, painted and stainless steel versions to meet different requirements in terms of mechanical strength, corrosion protection and suitability for specific environmental conditions of installation.



T0 113 0760

Length: 0

Coatings

- 01 Galvanization (Sendzimir method) - UNI EN 10346
- 03 Hot dip galvanizing - UNI EN ISO 1461
- 11 Grey RAL 7032 - ISO9227-ISO6270-ISO2810
- 15 Blue RAL 5015 - ISO9227-ISO6270-ISO2810
- 40 Stainless steel AISI 304 - UNI EN 10088
- 41 Stainless steel AISI 316L - UNI EN 10088

Technical Characteristics	
Dimension	
W (B)	600
Weight	
[Kg]	4,10
Technical Info	
a	205
w (b)	336
R	100

Certified System
- IMQ
- EN 61537-1 ed.2007
- EN 50085-1:2005 ed EN 50085-2-1:2006
- UL file E471266
Attention: for ZT and ZM material sold/assembled in U.S.A. and Canada, please require UL mark

Thickness

T1 113 - Component - 1,00mm

T1 114 - Cover - 0,80mm

***T0 113 0507 - Dimension on demand**

Certifications

