


“T” junction descending with Cover



Available in heights (H):

- 50
- 75
- 100

Dimension							Weight	Technical Info			Code
W (B)	01	03	11	15	40	41	[Kg]	a	w (b)	R	
75	01	03	11	15	40	41	1,20	205	336	100	T0 113 0707
100	01	03	11	15	40	41	1,34	205	336	100	T0 113 0710
150	01	03	11	15	40	41	1,62	205	336	100	T0 113 0715
200	01	03	11	15	40	41	1,89	205	336	100	T0 113 0720
300	01	03	11	15	40	41	2,44	205	336	100	T0 113 0730
400	01	03	11	15	40	41	3,00	205	336	100	T0 113 0740
500	01	03	11	15	40	41	3,55	205	336	100	T0 113 0750
600	01	03	11	15	40	41	4,10	205	336	100	T0 113 0760

Thickness

- T1 113 - Component - 1,00mm
- T1 114 - Cover - 0,80mm

***T0 113 0507 - Dimension on demand**

Certifications



List of Coatings

- Galvanization (Sendzimir method) - UNI EN 10346
- Hot dip galvanizing - UNI EN ISO 1461
- Grey RAL 7032 - ISO9227-ISO6270-ISO2810
- Blue RAL 5015 - ISO9227-ISO6270-ISO2810
- Stainless steel AISI 304 - UNI EN 10088
- Stainless steel AISI 316L - UNI EN 10088

Certified System

- IMQ
- EN 61537-1 ed.2007
- EN 50085-1:2005 ed EN 50085-2-1:2006
- UL file E471266
- Attention: for ZT and ZM material sold/assembled in U.S.A. and Canada, please require UL mark