


Rising skewed "T" junction with Cover



Available in heights (H):

50

75

100

Dimension							Weight	Technical Info			Code
W (B)							[Kg]	a	w (b)	R	
75	01	03	11	15	40	41	1,25	225	335	100	T0 119 0707
100	01	03	11	15	40	41	1,57	250	360	100	T0 119 0710
150	01	03	11	15	40	41	2,42	300	410	100	T0 119 0715
200	01	03	11	15	40	41	3,27	350	460	100	T0 119 0720
300	01	03	11	15	40	41	5,70	450	560	100	T0 119 0730
400	01	03	11	15	40	41	8,80	550	660	100	T0 119 0740
500	01	03	11	15	40	41	12,50	650	760	100	T0 119 0750
600	01	03	11	15	40	41	16,83	750	860	100	T0 119 0760

Thickness

T1 119 - Component - 1,00mm

T1 119 / T1 128 - Covers - 0,80mm

*T0 119 0507 - Dimension on demand

Certifications



E471266



List of Coatings

Galvanization (Sendzimir method) - UNI EN 10346

Hot dip galvanizing - UNI EN ISO 1461

Grey RAL 7032 - ISO9227-ISO6270-ISO2810

Blue RAL 5015 - ISO9227-ISO6270-ISO2810

Stainless steel AISI 304 - UNI EN 10088

Stainless steel AISI 316L - UNI EN 10088

Certified System

- IMQ

- EN 61537-1 ed.2007

- EN 50085-1:2005 ed EN 50085-2-1:2006

- UL file E471266

Attention: for ZT and ZM material sold/assembled in U.S.A. and Canada, please require UL mark