


Articulated vertical elbow



Available in heights (H):

50

75

100

Dimension							Weight	L	Code
W (B)	01	03	11	15	40	41	[Kg]	[mm]	
75	01	03	11	15	40	41	0,53	308	T0 129 0707
100	01	03	11	15	40	41	0,57	308	T0 129 0710
150	01	03	11	15	40	41	0,66	308	T0 129 0715
200	01	03	11	15	40	41	0,75	308	T0 129 0720
300	01	03	11	15	40	41	0,92	308	T0 129 0730
400	01	03	11	15	40	41	1,09	308	T0 129 0740
500	01	03	11	15	40	41	1,26	308	T0 129 0750
600	01	03	11	15	40	41	1,43	308	T0 129 0760

Thickness

Component - 1,00mm

*T0 129 0507 - Dimension on demand

Certifications



E471266



List of Coatings

Galvanization (Sendzimir method) - UNI EN 10346

Hot dip galvanizing - UNI EN ISO 1461

Grey RAL 7032 - ISO9227-ISO6270-ISO2810

Blue RAL 5015 - ISO9227-ISO6270-ISO2810

Stainless steel AISI 304 - UNI EN 10088

Stainless steel AISI 316L - UNI EN 10088

Certified System

- IMQ

- EN 61537-1 ed.2007

- EN 50085-1:2005 ed EN 50085-2-1:2006

- UL file E471266

Attention: for ZT and ZM material sold/assembled in U.S.A. and Canada, please require UL mark