


Skewed cross with Cover



Available in heights (H):

- 50
- 75
- 100

Dimension					Weight	Technical Info			Code
W (B)	01	03	11	15	[Kg]	a	w (b)	R	
100	01	03	11	15	2,10	400	360	100	T0 131 1010
150	01	03	11	15	3,18	500	410	100	T0 131 1015
200	01	03	11	15	4,50	600	460	100	T0 131 1020
300	01	03	11	15	7,87	800	560	100	T0 131 1030
400	01	03	11	15	12,23	1000	660	100	T0 131 1040
500	01	03	11	15	17,57	1200	760	100	T0 131 1050
600	01	03	11	15	23,90	1400	860	100	T0 131 1060

Thickness

- T1 131 - Component - 1,00mm
- T1 132 - Cover - 0,80mm

Certifications



List of Coatings

- Galvanization (Sendzimir method) - UNI EN 10346
- Hot dip galvanizing - UNI EN ISO 1461
- Grey RAL 7032 - ISO9227-ISO6270-ISO2810
- Blue RAL 5015 - ISO9227-ISO6270-ISO2810

Certified System

- IMQ
- EN 61537-1 ed.2007
- EN 50085-1:2005 ed EN 50085-2-1:2006
- UL file E471266
- Attention: for ZT and ZM material sold/assembled in U.S.A. and Canada, please require UL mark