


Skewed cross with Cover



Available in heights (H):

- 50
- 75
- 100

Dimension					Weight	Technical Info			Code
W (B)	01	03	11	15	[Kg]	a	w (b)	R	
75	01	03	11	15	1,64	375	335	100	T0 131 0707
100	01	03	11	15	2,09	425	360	100	T0 131 0710
150	01	03	11	15	3,19	525	410	100	T0 131 0715
200	01	03	11	15	4,54	625	460	100	T0 131 0720
300	01	03	11	15	7,96	825	560	100	T0 131 0730
400	01	03	11	15	12,37	1025	660	100	T0 131 0740
500	01	03	11	15	16,17	1225	760	100	T0 131 0750
600	01	03	11	15	24,13	1425	860	100	T0 131 0760

**Thickness**

- T1 131 - Component - 1,00mm
- T1 132 - Cover - 0,80mm

**Certifications**



List of Coatings	
	Galvanization (Sendzimir method) - UNI EN 10346
	Hot dip galvanizing - UNI EN ISO 1461
	Grey RAL 7032 - ISO9227-ISO6270-ISO2810
	Blue RAL 5015 - ISO9227-ISO6270-ISO2810

Certified System
- IMQ
- EN 61537-1 ed.2007
- EN 50085-1:2005 ed EN 50085-2-1:2006
- UL file E471266
Attention: for ZT and ZM material sold/assembled in U.S.A. and Canada, please require UL mark