


Inside "U" joint



Available in heights (H):

- 50
- 75
- 100

Dimension					Weight	Technical Info			Code	
W (B)	01	03	11	15	40	[Kg]	a	w (b)	L	
75	01	03	11	15	40	0,13	70	72	52	T0 203 0707
100	01	03	11	15	40	0,15	70	97	52	T0 203 0710
150	01	03	11	15	40	0,18	70	147	52	T0 203 0715
200	01	03	11	15	40	0,21	70	197	52	T0 203 0720
300	01	03	11	15	40	0,27	70	296	52	T0 203 0730
400	01	03	11	15	40	0,33	70	396	52	T0 203 0740
500	01	03	11	15	40	0,39	70	496	52	T0 203 0750
600	01	03	11	15	40	0,45	70	596	52	T0 203 0760

Certifications



List of Coatings

- Galvanization (Sendzimir method) - UNI EN 10346
- Hot dip galvanizing - UNI EN ISO 1461
- Grey RAL 7032 - ISO9227-ISO6270-ISO2810
- Blue RAL 5015 - ISO9227-ISO6270-ISO2810
- Stainless steel AISI 304 - UNI EN 10088

Certified System


- IMQ
- EN 61537-1 ed.2007
- EN 50085-1:2005 ed EN 50085-2-1:2006
- UL file E471266
- Attention: for ZT and ZM material sold/assembled in U.S.A. and Canada, please require UL mark

Inside "U" joint

Assembly

H50		n. 4 M6x10 / M6x12	T0 620 0610 / T0 620 0612
		n. 4 M6	T0 621 0600
H75-100		n. 8 M6x10 / M6x12	T0 620 0610 / T0 620 0612
		n. 8 M6	T0 621 0600

Not included



In the case of the installation of internal "U" joints on painted items, preparation with equipotential plates is required.