


Flange for panel mount



Available in heights (H):

50

75

100

Dimension					Thickness	Weight	Technical Info				Code	
W (B)	01	03	11	15	40	[mm]	[Kg]	a	w (b)	c	d	
100	01	03	11	15	40	1,50	0,21	150	150	125	125	T0 260 1010
150	01	03	11	15	40	1,50	0,25	150	200	175	125	T0 260 1015
200	01	03	11	15	40	1,50	0,29	150	250	225	125	T0 260 1020
300	01	03	11	15	40	1,50	0,36	150	350	325	125	T0 260 1030
400	01	03	11	15	40	1,50	0,44	150	450	425	125	T0 260 1040
500	01	03	11	15	40	1,50	0,52	150	550	525	125	T0 260 1050
600	01	03	11	15	40	1,50	0,59	150	650	625	125	T0 260 1060

Certifications



E471266



List of Coatings

Galvanization (Sendzimir method) - UNI EN 10346

Hot dip galvanizing - UNI EN ISO 1461

Grey RAL 7032 - ISO9227-ISO6270-ISO2810

Blue RAL 5015 - ISO9227-ISO6270-ISO2810

Stainless steel AISI 304 - UNI EN 10088

Certified System

- IMQ

- EN 61537-1 ed.2007

- EN 50085-1:2005 ed EN 50085-2-1:2006

- UL file E471266

Attention: for ZT and ZM material sold/assembled in U.S.A. and Canada, please require UL mark

Flange for panel mount

Assembly

H 50		n. 2 M6x10 / M6x12	T0 620 0610 / T0 620 0612
		n. 2 M6	T0 621 0600
for each flange			
H 75- 100		n. 4 M6x10 / M6x12	T0 620 0610 / T0 620 0612
		n. 4 M6	T0 621 0600
for each flange			

Not included

