


Flange for panel mount



T0 260 1010

Length: 0

Coatings

- 01 Galvanization (Sendzimir method) - UNI EN 10346
- 03 Hot dip galvanizing - UNI EN ISO 1461
- 11 Grey RAL 7032 - ISO9227-ISO6270-ISO2810
- 15 Blue RAL 5015 - ISO9227-ISO6270-ISO2810
- 40 Stainless steel AISI 304 - UNI EN 10088

| Technical Characteristics | |
|---------------------------|------|
| Dimension | |
| W (B) | 100 |
| Thickness | |
| [mm] | 1,50 |
| Weight | |
| [Kg] | 0,21 |
| Technical Info | |
| a | 150 |
| w (b) | 150 |
| c | 125 |
| d | 125 |

| Certified System |
|---|
| - IMQ |
| - EN 61537-1 ed.2007 |
| - EN 50085-1:2005 ed EN 50085-2-1:2006 |
| - UL file E471266 |
| Attention: for ZT and ZM material sold/assembled in U.S.A. and Canada, please require UL mark |

Certifications



Flange for panel mount

Assembly

| | | | |
|-----------------|---|-----------------------|--------------------------------------|
| H 50 |  | n. 2 M6x10 / M6x12 | T0 620 0610 / T0 620 0612 |
| |  | n. 2 M6 | T0 621 0600 |
| for each flange | | | |
| H 75- 100 |  | n. 4 M6x10 / M6x12 | T0 620 0610 / T0 620 0612 |
| |  | n. 4 M6 | T0 621 0600 |
| for each flange | | | |

Not included

