


## Flange for panel mount



TO 260 1030

Length: 0

Coatings

- 01 Galvanization (Sendzimir method) - UNI EN 10346
- 03 Hot dip galvanizing - UNI EN ISO 1461
- 11 Grey RAL 7032 - ISO9227-ISO6270-ISO2810
- 15 Blue RAL 5015 - ISO9227-ISO6270-ISO2810
- 40 Stainless steel AISI 304 - UNI EN 10088

Technical Characteristics	
Dimension	
W (B)	300
Thickness	
[mm]	1,50
Weight	
[Kg]	0,36
Technical Info	
a	150
w (b)	350
c	325
d	125

Certified System
- IMQ
- EN 61537-1 ed.2007
- EN 50085-1:2005 ed EN 50085-2-1:2006
- UL file E471266
Attention: for ZT and ZM material sold/assembled in U.S.A. and Canada, please require UL mark

Certifications



## Flange for panel mount

### Assembly

H 50		n. 2 M6x10 / M6x12	<b>T0 620 0610 / T0 620 0612</b>
		n. 2 M6	<b>T0 621 0600</b>
for each flange			
H 75- 100		n. 4 M6x10 / M6x12	<b>T0 620 0610 / T0 620 0612</b>
		n. 4 M6	<b>T0 621 0600</b>
for each flange			

*Not included*

