


Flange for panel mount



Available in heights (H):

- 50
- 75
- 100

Dimension					Thickness	Weight	Technical Info				Code	
W (B)					[mm]	[Kg]	a	w (b)	c	d		
75	01	03	11	15	40	1,50	0,16	125	125	100	100	T0 260 0707
100	01	03	11	15	40	1,50	0,18	125	150	125	100	T0 260 0710
150	01	03	11	15	40	1,50	0,22	125	200	175	100	T0 260 0715
200	01	03	11	15	40	1,50	0,25	125	250	225	100	T0 260 0720
300	01	03	11	15	40	1,50	0,33	125	350	325	100	T0 260 0730
400	01	03	11	15	40	1,50	0,41	125	450	425	100	T0 260 0740
500	01	03	11	15	40	1,50	0,48	125	550	525	100	T0 260 0750
600	01	03	11	15	40	1,50	0,56	125	650	625	100	T0 260 0760

Certifications



List of Coatings

- Galvanization (Sendzimir method) - UNI EN 10346
- Hot dip galvanizing - UNI EN ISO 1461
- Grey RAL 7032 - ISO9227-ISO6270-ISO2810
- Blue RAL 5015 - ISO9227-ISO6270-ISO2810
- Stainless steel AISI 304 - UNI EN 10088

Certified System

- IMQ
- EN 61537-1 ed.2007
- EN 50085-1:2005 ed EN 50085-2-1:2006
- UL file E471266
- Attention: for ZT and ZM material sold/assembled in U.S.A. and Canada, please require UL mark

Flange for panel mount

Assembly

H 50		n. 2 M6x10 / M6x12	T0 620 0610 / T0 620 0612
		n. 2 M6	T0 621 0600
for each flange			
H 75- 100		n. 4 M6x10 / M6x12	T0 620 0610 / T0 620 0612
		n. 4 M6	T0 621 0600
for each flange			

Not included

