


## Flange for reducer for panel mount



Available in heights (H):

50

75

100

Dimension					Thickness	Weight	Technical Info				Code	
W (B)	01	03	11	15	40	[mm]	[Kg]	a	w (b)	c	d	
100	01	03	11	15	40	1,50	0,16	125	150	125	100	T0 261 1010
150	01	03	11	15	40	1,50	0,17	125	200	175	100	T0 261 1015
200	01	03	11	15	40	1,50	0,19	125	250	225	100	T0 261 1020
300	01	03	11	15	40	1,50	0,23	125	350	325	100	T0 261 1030
400	01	03	11	15	40	1,50	0,27	125	450	425	100	T0 261 1040
500	01	03	11	15	40	1,50	0,31	125	550	525	100	T0 261 1050
600	01	03	11	15	40	1,50	0,35	125	650	625	100	T0 261 1060

### Certifications



E471266



### List of Coatings

Galvanization (Sendzimir method) - UNI EN 10346

Hot dip galvanizing - UNI EN ISO 1461

Grey RAL 7032 - ISO9227-ISO6270-ISO2810

Blue RAL 5015 - ISO9227-ISO6270-ISO2810

Stainless steel AISI 304 - UNI EN 10088

### Certified System

- IMQ

- EN 61537-1 ed.2007

- EN 50085-1:2005 ed EN 50085-2-1:2006

- UL file E471266

Attention: for ZT and ZM material sold/assembled in U.S.A. and Canada, please require UL mark

## Flange for reducer for panel mount

### Assembly

H 50		n. 2 M6x10 / M6x12	<b>TO 620 0610 / TO 620 0612</b>
		n. 2 M6	<b>TO 621 0600</b>
for each flange			
H 75- 100		n. 4 M6x10 / M6x12	<b>TO 620 0610 / TO 620 0612</b>
		n. 4 M6	<b>TO 621 0600</b>
for each flange			

*Not included*

