


Right Reducer



Available in heights (H):

- 50
- 75
- 100

Dimension						Thickness	Weight	Code
W (B)	01	03	11	15	40	[mm]	[Kg]	
37,5	01	03	11	15	40	1,00	0,04	TO 262 0703
50	01	03	11	15	40	1,00	0,05	TO 262 0705
75	01	03	11	15	40	1,00	0,07	TO 262 0707
100	01	03	11	15	40	1,00	0,08	TO 262 0710
150	01	03	11	15	40	1,00	0,12	TO 262 0715

Certifications



E471266



List of Coatings

- Galvanization (Sendzimir method) - UNI EN 10346
- Hot dip galvanizing - UNI EN ISO 1461
- Grey RAL 7032 - ISO9227-ISO6270-ISO2810
- Blue RAL 5015 - ISO9227-ISO6270-ISO2810
- Stainless steel AISI 304 - UNI EN 10088

Certified System

- IMQ
- EN 61537-1 ed.2007
- EN 50085-1:2005 ed EN 50085-2-1:2006
- UL file E471266
- Attention: for ZT and ZM material sold/assembled in U.S.A. and Canada, please require UL mark

Right Reducer

Assembly

 n. 4 M6x10 / M6x12 **T0 620 0610 / T0 620 0620**

 n. 4 M6 **T0 621 0600**

Not included

