


## Right Reducer with Cover



Available in heights (H):

50

75

100

							Weight	Technical Info	Reduction from	Code
						[Kg]	L	W (B)	W1 (B1)	
01	03	11	15	40	41	0,63	220	150	100	T1 073 3433
01	03	11	15	40	41	0,72	220	200	150	T1 073 3534
01	03	11	15	40	41	0,85	220	300	200	T1 073 3635
01	03	11	15	40	41	1,03	220	400	300	T1 073 3736
01	03	11	15	40	41	1,20	220	500	400	T1 073 3837
01	03	11	15	40	41	1,37	220	600	500	T1 073 3938

### Thickness

Component - 1,00mm

### Certifications



E471266



### List of Coatings

Galvanization (Sendzimir method) - UNI EN 10346

Hot dip galvanizing - UNI EN ISO 1461

Grey RAL 7032 - ISO9227-ISO6270-ISO2810

Blue RAL 5015 - ISO9227-ISO6270-ISO2810

Stainless steel AISI 304 - UNI EN 10088

Stainless steel AISI 316L - UNI EN 10088

### Certified System

- IMQ

- EN 61537-1 ed.2007

- EN 50085-1:2005 ed EN 50085-2-1:2006

- UL file E471266

Attention: for ZT and ZM material sold/assembled in U.S.A. and Canada, please require UL mark