


### 45° flat elbow without Cover



Available in heights (H):

- 50
- 75
- 100

Dimension							Weight	Technical Info			Code
W (B)	01	03	11	15	40	41	[Kg]	a	w (b)	R	
75	01	03	11	15	40	41	0,35	175	124	100	T1 087 0707
100	01	03	11	15	40	41	0,41	192	149	100	T1 087 0710
150	01	03	11	15	40	41	0,54	228	199	100	T1 087 0715
200	01	03	11	15	40	41	0,68	263	249	100	T1 087 0720
300	01	03	11	15	40	41	1,02	334	349	100	T1 087 0730
400	01	03	11	15	40	41	1,42	404	449	100	T1 087 0740
500	01	03	11	15	40	41	1,88	475	549	100	T1 087 0750
600	01	03	11	15	40	41	2,41	546	649	100	T1 087 0760

#### Thickness

Component - 1,00mm

#### Certifications



E471266



#### List of Coatings

Galvanization (Sendzimir method) - UNI EN 10346

Hot dip galvanizing - UNI EN ISO 1461

Grey RAL 7032 - ISO9227-ISO6270-ISO2810

Blue RAL 5015 - ISO9227-ISO6270-ISO2810

Stainless steel AISI 304 - UNI EN 10088

Stainless steel AISI 316L - UNI EN 10088

#### Certified System

- IMQ
- EN 61537-1 ed.2007
- EN 50085-1:2005 ed EN 50085-2-1:2006
- UL file E471266
- Attention: for ZT and ZM material sold/assembled in U.S.A. and Canada, please require UL mark