


45° Inside Elbow without Cover



Available in heights (H):

50

75

100

Dimension							Weight	Technical Info	Code
W (B)							[Kg]	a w (b) R	
75	01	03	11	15	40	41	0,37	126 175 100	T1 093 0707
100	01	03	11	15	40	41	0,41	126 175 100	T1 093 0710
150	01	03	11	15	40	41	0,48	126 175 100	T1 093 0715
200	01	03	11	15	40	41	0,56	126 175 100	T1 093 0720
300	01	03	11	15	40	41	0,71	126 175 100	T1 093 0730
400	01	03	11	15	40	41	0,87	126 175 100	T1 093 0740
500	01	03	11	15	40	41	1,02	126 175 100	T1 093 0750
600	01	03	11	15	40	41	1,18	126 175 100	T1 093 0760

Thickness

Component - 1,00mm

Certifications



E471266



List of Coatings

Galvanization (Sendzimir method) - UNI EN 10346

Hot dip galvanizing - UNI EN ISO 1461

Grey RAL 7032 - ISO9227-ISO6270-ISO2810

Blue RAL 5015 - ISO9227-ISO6270-ISO2810

Stainless steel AISI 304 - UNI EN 10088

Stainless steel AISI 316L - UNI EN 10088

Certified System

- IMQ
- EN 61537-1 ed.2007
- EN 50085-1:2005 ed EN 50085-2-1:2006
- UL file E471266

Attention: for ZT and ZM material sold/assembled in U.S.A. and Canada, please require UL mark