


## 30° Inside Elbow without Cover



T1 095 1040

Length: 0

Coatings

- 01 Galvanization (Sendzimir method) - UNI EN 10346
- 03 Hot dip galvanizing - UNI EN ISO 1461
- 11 Grey RAL 7032 - ISO9227-ISO6270-ISO2810
- 15 Blue RAL 5015 - ISO9227-ISO6270-ISO2810
- 40 Stainless steel AISI 304 - UNI EN 10088
- 41 Stainless steel AISI 316L - UNI EN 10088

| Technical Characteristics |      |
|---------------------------|------|
| Dimension                 |      |
| W (B)                     | 400  |
| Weight                    |      |
| [Kg]                      | 0,71 |
| Technical Info            |      |
| a                         | 130  |
| w (b)                     | 156  |
| R                         | 100  |

| Certified System                                                                                                                                                                                                                                                      |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <ul style="list-style-type: none"> <li>- IMQ</li> <li>- EN 61537-1 ed.2007</li> <li>- EN 50085-1:2005 ed EN 50085-2-1:2006</li> <li>- UL file E471266</li> </ul> <p>Attention: for ZT and ZM material sold/assembled in U.S.A. and Canada, please require UL mark</p> |

Certifications

### Thickness

Component - 1,00mm

