


## 90° Vertical inside/outside elbow without Cover



Available in heights (H):

50

75

100

| Dimension |    |    |    |    |    |    | Weight | Technical Info | Code |
|-----------|----|----|----|----|----|----|--------|----------------|------|
| W (B)     |    |    |    |    |    |    | [Kg]   | a              | R    |
| 75        | 01 | 03 | 11 | 15 | 40 | 41 | 0,61   | 205            | 100  |
| 100       | 01 | 03 | 11 | 15 | 40 | 41 | 0,70   | 205            | 100  |
| 150       | 01 | 03 | 11 | 15 | 40 | 41 | 0,88   | 205            | 100  |
| 200       | 01 | 03 | 11 | 15 | 40 | 41 | 1,06   | 205            | 100  |
| 300       | 01 | 03 | 11 | 15 | 40 | 41 | 1,42   | 205            | 100  |
| 400       | 01 | 03 | 11 | 15 | 40 | 41 | 1,78   | 205            | 100  |
| 500       | 01 | 03 | 11 | 15 | 40 | 41 | 2,14   | 205            | 100  |
| 600       | 01 | 03 | 11 | 15 | 40 | 41 | 2,50   | 205            | 100  |

### Thickness

Component - 1,00mm

### Certifications



E471266



### List of Coatings

Galvanization (Sendzimir method) - UNI EN 10346

Hot dip galvanizing - UNI EN ISO 1461

Grey RAL 7032 - ISO9227-ISO6270-ISO2810

Blue RAL 5015 - ISO9227-ISO6270-ISO2810

Stainless steel AISI 304 - UNI EN 10088

Stainless steel AISI 316L - UNI EN 10088

### Certified System

- IMQ
- EN 61537-1 ed.2007
- EN 50085-1:2005 ed EN 50085-2-1:2006
- UL file E471266

Attention: for ZT and ZM material sold/assembled in U.S.A. and Canada, please require UL mark