


“T” side outlet without Cover



Available in heights (H):

- 50
- 75
- 100

| Dimension |    |    |    |    |    |    | Weight | Technical Info |       |     | Code        |
|-----------|----|----|----|----|----|----|--------|----------------|-------|-----|-------------|
| W (B)     | 01 | 03 | 11 | 15 | 40 | 41 | [Kg]   | a              | w (b) | R   |             |
| 100       | 01 | 03 | 11 | 15 | 40 | 41 | 0,65   | 160            | 360   | 100 | T1 109 1010 |
| 150       | 01 | 03 | 11 | 15 | 40 | 41 | 0,72   | 160            | 410   | 100 | T1 109 1015 |
| 200       | 01 | 03 | 11 | 15 | 40 | 41 | 0,78   | 160            | 460   | 100 | T1 109 1020 |
| 300       | 01 | 03 | 11 | 15 | 40 | 41 | 0,90   | 160            | 560   | 100 | T1 109 1030 |
| 400       | 01 | 03 | 11 | 15 | 40 | 41 | 1,03   | 160            | 660   | 100 | T1 109 1040 |
| 500       | 01 | 03 | 11 | 15 | 40 | 41 | 1,16   | 160            | 760   | 100 | T1 109 1050 |
| 600       | 01 | 03 | 11 | 15 | 40 | 41 | 1,28   | 160            | 860   | 100 | T1 109 1060 |

**Thickness**

Component - 1,00mm

Certifications



E471266



List of Coatings

- Galvanization (Sendzimir method) - UNI EN 10346
- Hot dip galvanizing - UNI EN ISO 1461
- Grey RAL 7032 - ISO9227-ISO6270-ISO2810
- Blue RAL 5015 - ISO9227-ISO6270-ISO2810
- Stainless steel AISI 304 - UNI EN 10088
- Stainless steel AISI 316L - UNI EN 10088

Certified System

- IMQ
- EN 61537-1 ed.2007
- EN 50085-1:2005 ed EN 50085-2-1:2006
- UL file E471266
- Attention: for ZT and ZM material sold/assembled in U.S.A. and Canada, please require UL mark