


## Rising skewed "T" junction without Cover



Available in heights (H):

50

75

100

Dimension	Weight						Technical Info			Code
W (B)	01	03	11	15	40	41	[Kg]	a	w (b)	R
100	01	03	11	15	40	41	1,45	250	360	100 T1 119 1010
150	01	03	11	15	40	41	2,07	300	410	100 T1 119 1015
200	01	03	11	15	40	41	2,80	350	460	100 T1 119 1020
300	01	03	11	15	40	41	4,63	450	560	100 T1 119 1030
400	01	03	11	15	40	41	7,15	550	660	100 T1 119 1040
500	01	03	11	15	40	41	9,69	650	760	100 T1 119 1050
600	01	03	11	15	40	41	12,93	750	860	100 T1 119 1060

### Thickness

Component - 1,00mm

### Certifications



E471266



### List of Coatings

Galvanization (Sendzimir method) - UNI EN 10346

Hot dip galvanizing - UNI EN ISO 1461

Grey RAL 7032 - ISO9227-ISO6270-ISO2810

Blue RAL 5015 - ISO9227-ISO6270-ISO2810

Stainless steel AISI 304 - UNI EN 10088

Stainless steel AISI 316L - UNI EN 10088

### Certified System

- IMQ
- EN 61537-1 ed.2007
- EN 50085-1:2005 ed EN 50085-2-1:2006
- UL file E471266

Attention: for ZT and ZM material sold/assembled in U.S.A. and Canada, please require UL mark