


90° left descending skewed elbow without Cover



Available in heights (H):

50

75

100

Dimension							Weight	Technical Info	Code
W (B)							[Kg]	a w (b) R	
50	01	03	11	15	40	41	0,46	200 180 100	T1 121 0505
100	01	03	11	15	40	41	0,79	250 230 100	T1 121 0510
150	01	03	11	15	40	41	1,19	300 280 100	T1 121 0515
200	01	03	11	15	40	41	1,67	350 330 100	T1 121 0520
300	01	03	11	15	40	41	2,88	450 430 100	T1 121 0530
400	01	03	11	15	40	41	4,39	550 530 100	T1 121 0540
500	01	03	11	15	40	41	6,22	650 630 100	T1 121 0550
600	01	03	11	15	40	41	8,37	750 730 100	T1 121 0560

Thickness

Component - 1,00mm

Certifications



E471266



List of Coatings

Galvanization (Sendzimir method) - UNI EN 10346

Hot dip galvanizing - UNI EN ISO 1461

Grey RAL 7032 - ISO9227-ISO6270-ISO2810

Blue RAL 5015 - ISO9227-ISO6270-ISO2810

Stainless steel AISI 304 - UNI EN 10088

Stainless steel AISI 316L - UNI EN 10088

Certified System

- IMQ
- EN 61537-1 ed.2007
- EN 50085-1:2005 ed EN 50085-2-1:2006
- UL file E471266

Attention: for ZT and ZM material sold/assembled in U.S.A. and Canada, please require UL mark