



Curva snodata verticale



Disponibile nelle altezze (H):

50

75

100

Dimensione						Peso	L	Codice
B						[Kg]	[mm]	
50	01	03	11	15	40	41	0,32	268 T0 129 0505
100	01	03	11	15	40	41	0,39	268 T0 129 0510
150	01	03	11	15	40	41	0,47	268 T0 129 0515
200	01	03	11	15	40	41	0,55	268 T0 129 0520
300	01	03	11	15	40	41	0,71	268 T0 129 0530
400	01	03	11	15	40	41	0,87	268 T0 129 0540
500	01	03	11	15	40	41	1,02	268 T0 129 0550
600	01	03	11	15	40	41	1,77	268 T0 129 0560

Spessori

Componente - 1,00mm

*T0 129 0507 - Misura a richiesta

Certificazioni



E471266



Legenda Trattamenti

Zincato Sendzimir - UNI EN 10346

Zincatura a caldo per immersione - UNI EN ISO 1461

Grigio RAL 7032 - ISO9227-ISO6270-ISO2810

Blu RAL 5015 - ISO9227-ISO6270-ISO2810

Inox AISI 304 - UNI EN 10088

Inox AISI 316L - UNI EN 10088

Sistema Certificato

- IMQ

- EN 61537-1 ed.2007

- EN 50085-1:2005 ed EN 50085-2-1:2006

- UL file E471266

Attenzione: per materiale Serie ZT e ZM
venduto/installato in USA e Canada, richiedere la
marcatura UL