


Raccordo a 4 vie con Coperchio



Disponibile nelle altezze (H):

50

75

100

Dimensione		Peso	Dati Tecnici	Codice
B		[Kg]	a b R	
50	01 03 11 15	1,19	350 310 100	T0 131 0505
100	01 03 11 15	2,07	450 360 100	T0 131 0510
150	01 03 11 15	3,19	550 410 100	T0 131 0515
200	01 03 11 15	4,56	650 460 100	T0 131 0520
300	01 03 11 15	8,03	850 560 100	T0 131 0530
400	01 03 11 15	12,48	1050 660 100	T0 131 0540
500	01 03 11 15	17,92	1250 760 100	T0 131 0550
600	01 03 11 15	24,35	1450 860 100	T0 131 0560

Spessori

T1 131 - Componente - 1,00mm

T1 132 - Coperchio - 0,80mm

Certificazioni



E471266



Legenda Trattamenti

Zincato Sendzimir - UNI EN 10346

Zincatura a caldo per immersione - UNI EN ISO 1461

Grigio RAL 7032 - ISO9227-ISO6270-ISO2810

Blu RAL 5015 - ISO9227-ISO6270-ISO2810

Sistema Certificato

- IMQ
- EN 61537-1 ed.2007
- EN 50085-1:2005 ed EN 50085-2-1:2006
- UL file E471266

Attenzione: per materiale Serie ZT e ZM venduto/installato in USA e Canada, richiedere la marcatura UL