


Chiusura di estremità



Disponibile nelle altezze (H):

50

75

100

Dimensione						Spessore	Peso	Dati Tecnici		Codice
B						[mm]	[Kg]	a	b	
100	01	03	11	15	40	1,00	0,11	101	103	T0 250 1010
150	01	03	11	15	40	1,00	0,16	101	153	T0 250 1015
200	01	03	11	15	40	1,00	0,20	101	203	T0 250 1020
300	01	03	11	15	40	1,00	0,29	101	303	T0 250 1030
400	01	03	11	15	40	1,00	0,37	101	403	T0 250 1040
500	01	03	11	15	40	1,00	0,46	101	503	T0 250 1050
600	01	03	11	15	40	1,00	0,54	101	603	T0 250 1060

Certificazioni



E471266



Legenda Trattamenti

Zincato Sendzimir - UNI EN 10346

Zincatura a caldo per immersione - UNI EN ISO 1461

Grigio RAL 7032 - ISO9227-ISO6270-ISO2810

Blu RAL 5015 - ISO9227-ISO6270-ISO2810

Inox AISI 304 - UNI EN 10088

Sistema Certificato

- IMQ
 - EN 61537-1 ed.2007
 - EN 50085-1:2005 ed EN 50085-2-1:2006
 - UL file E471266
 Attenzione: per materiale Serie ZT e ZM
 venduto/installato in USA e Canada, richiedere la
 marcatura UL

Chiusura di estremità

Montaggio

H 50		n. 2 M6x10 / M6x12	T0 620 0610 / T0 620 0612
		n. 2 M6	T0 621 0600
		per ogni giunto	
H 75-100		n. 4 M6x10 / M6x12	T0 620 0610 / T0 620 0612
		n. 4 M6	T0 621 0600
		per ogni giunto	

Non compresi

