


## Flangia per attacco a quadro



T0 260 0505

Lunghezza: 0

Finiture

- 01 Zincato Sendzimir - UNI EN 10346
- 03 Zincatura a caldo per immersione - UNI EN ISO 1461
- 11 Grigio RAL 7032 - ISO9227-ISO6270-ISO2810
- 15 Blu RAL 5015 - ISO9227-ISO6270-ISO2810
- 40 Inox AISI 304 - UNI EN 10088

### Caratteristiche Tecniche

#### Dimensione

B 50

#### Spessore

[mm] 1,50

#### Peso

[Kg] 0,11

#### Dati Tecnici

a 100

b 100

c 75

d 75

### Sistema Certificato

- IMQ
  - EN 61537-1 ed.2007
  - EN 50085-1:2005 ed EN 50085-2-1:2006
  - UL file E471266
- Attenzione: per materiale Serie ZT e ZM venduto/installato in USA e Canada, richiedere la marcatura UL

### Certificazioni



## Flangia per attacco a quadro

### Montaggio

|          |                                                                                   |                    |                                  |
|----------|-----------------------------------------------------------------------------------|--------------------|----------------------------------|
| H 50     |  | n. 2 M6x10 / M6x12 | <b>T0 620 0610 / T0 620 0612</b> |
|          |  | n. 2 M6            | <b>T0 621 0600</b>               |
|          |                                                                                   | per ogni flangia   |                                  |
| H 75-100 |  | n. 4 M6x10 / M6x12 | <b>T0 620 0610 / T0 620 0612</b> |
|          |  | n. 4 M6            | <b>T0 621 0600</b>               |
|          |                                                                                   | per ogni flangia   |                                  |

Non compresi

