


Flangia per attacco a quadro



T0 260 0510

Lunghezza: 0

Finiture

- 01 Zincato Sendzimir - UNI EN 10346
- 03 Zincatura a caldo per immersione - UNI EN ISO 1461
- 11 Grigio RAL 7032 - ISO9227-ISO6270-ISO2810
- 15 Blu RAL 5015 - ISO9227-ISO6270-ISO2810
- 40 Inox AISI 304 - UNI EN 10088

Caratteristiche Tecniche

Dimensione

B 100

Spessore

[mm] 1,50

Peso

[Kg] 0,15

Dati Tecnici

a 100

b 150


c 125

d 75

Sistema Certificato

- IMQ
 - EN 61537-1 ed.2007
 - EN 50085-1:2005 ed EN 50085-2-1:2006
 - UL file E471266
- Attenzione: per materiale Serie ZT e ZM venduto/installato in USA e Canada, richiedere la marcatura UL

Certificazioni



Flangia per attacco a quadro

Montaggio

H 50		n. 2 M6x10 / M6x12	T0 620 0610 / T0 620 0612
		n. 2 M6	T0 621 0600
		per ogni flangia	
H 75-100		n. 4 M6x10 / M6x12	T0 620 0610 / T0 620 0612
		n. 4 M6	T0 621 0600
		per ogni flangia	

Non compresi

