


Flangia di riduzione per attacco a quadro



Disponibile nelle altezze (H):

50

75

100

Dimensione		Spessore	Peso	Dati Tecnici	Codice
B		[mm]	[Kg]	a b c d	
100	01 03 11 15 40	1,50	0,16	125 150 125 100	T0 261 1010
150	01 03 11 15 40	1,50	0,17	125 200 175 100	T0 261 1015
200	01 03 11 15 40	1,50	0,19	125 250 225 100	T0 261 1020
300	01 03 11 15 40	1,50	0,23	125 350 325 100	T0 261 1030
400	01 03 11 15 40	1,50	0,27	125 450 425 100	T0 261 1040
500	01 03 11 15 40	1,50	0,31	125 550 525 100	T0 261 1050
600	01 03 11 15 40	1,50	0,35	125 650 625 100	T0 261 1060

Certificazioni



Legenda Trattamenti

	Zincato Sendzimir - UNI EN 10346
	Zincatura a caldo per immersione - UNI EN ISO 1461
	Grigio RAL 7032 - ISO9227-ISO6270-ISO2810
	Blu RAL 5015 - ISO9227-ISO6270-ISO2810
	Inox AISI 304 - UNI EN 10088

Sistema Certificato

- IMQ
- EN 61537-1 ed.2007
- EN 50085-1:2005 ed EN 50085-2-1:2006
- UL file E471266
Attenzione: per materiale Serie ZT e ZM
venduto/installato in USA e Canada, richiedere la
marcatatura UL

Flangia di riduzione per attacco a quadro

Montaggio

H 50		n. 2 M6x10 / M6x12	T0 620 0610 / T0 620 0612
		n. 2 M6	T0 621 0600
		per ogni flangia	
H 75-100		n. 4 M6x10 / M6x12	T0 620 0610 / T0 620 0612
		n. 4 M6	T0 621 0600
		per ogni flangia	

Non compresi

