



Riduzione Sinistra senza Coperchio



Disponibile nelle altezze (H):

50

75

100

						Peso	Dati Tecnici	Riduzione da		Codice
						[Kg]	L	B	B1	
01	03	11	15	40	41	0,36	220	100	50	T1 075 1311
01	03	11	15	40	41	0,46	220	150	100	T1 075 1413
01	03	11	15	40	41	0,55	220	200	150	T1 075 1514
01	03	11	15	40	41	0,68	220	300	200	T1 075 1615
01	03	11	15	40	41	0,85	220	400	300	T1 075 1716
01	03	11	15	40	41	1,02	220	500	400	T1 075 1817
01	03	11	15	40	41	1,20	220	600	500	T1 075 1918

Spessori

Componente - 1,00mm

Certificazioni



E471266



Legenda Trattamenti

Zincato Sendzimir - UNI EN 10346

Zincatura a caldo per immersione - UNI EN ISO 1461

Grigio RAL 7032 - ISO9227-ISO6270-ISO2810

Blu RAL 5015 - ISO9227-ISO6270-ISO2810

Inox AISI 304 - UNI EN 10088

Inox AISI 316L - UNI EN 10088

Sistema Certificato

- IMQ
- EN 61537-1 ed.2007
- EN 50085-1:2005 ed EN 50085-2-1:2006
- UL file E471266

Attenzione: per materiale Serie ZT e ZM venduto/installato in USA e Canada, richiedere la marcatura UL