


Curva Piana 30° senza Coperchio



Disponibile nelle altezze (H):

50

75

100

Dimensione						Peso	Dati Tecnici			Codice
B						[Kg]	a	b	R	
100	01	03	11	15	40	41	0,37	156	127	100 T1 089 1010
150	01	03	11	15	40	41	0,47	181	177	100 T1 089 1015
200	01	03	11	15	40	41	0,57	206	227	100 T1 089 1020
300	01	03	11	15	40	41	0,82	256	327	100 T1 089 1030
400	01	03	11	15	40	41	1,10	306	427	100 T1 089 1040
500	01	03	11	15	40	41	1,43	356	527	100 T1 089 1050
600	01	03	11	15	40	41	1,80	406	627	100 T1 089 1060

Spessori

Componente - 1,00mm

Certificazioni



E471266



Legenda Trattamenti

Zincato Sendzimir - UNI EN 10346

Zincatura a caldo per immersione - UNI EN ISO 1461

Grigio RAL 7032 - ISO9227-ISO6270-ISO2810

Blu RAL 5015 - ISO9227-ISO6270-ISO2810

Inox AISI 304 - UNI EN 10088

Inox AISI 316L - UNI EN 10088

Sistema Certificato

- IMQ
- EN 61537-1 ed.2007
- EN 50085-1:2005 ed EN 50085-2-1:2006
- UL file E471266

Attenzione: per materiale Serie ZT e ZM venduto/installato in USA e Canada, richiedere la marcatura UL