



Curva Salita 90° senza Coperchio



Disponibile nelle altezze (H):

50

75

100

Dimensione							Peso	Dati Tecnici			Codice
B							[Kg]	a	R		
50	01	03	11	15	40	41	0,39	180	100	T1 091 0505	
100	01	03	11	15	40	41	0,50	180	100	T1 091 0510	
150	01	03	11	15	40	41	0,62	180	100	T1 091 0515	
200	01	03	11	15	40	41	0,73	180	100	T1 091 0520	
300	01	03	11	15	40	41	0,96	180	100	T1 091 0530	
400	01	03	11	15	40	41	1,19	180	100	T1 091 0540	
500	01	03	11	15	40	41	1,42	180	100	T1 091 0550	
600	01	03	11	15	40	41	1,65	180	100	T1 091 0560	

Spessori

Componente - 1,00mm

Certificazioni



E471266



Legenda Trattamenti

Zincato Sendzimir - UNI EN 10346

Zincatura a caldo per immersione - UNI EN ISO 1461

Grigio RAL 7032 - ISO9227-ISO6270-ISO2810

Blu RAL 5015 - ISO9227-ISO6270-ISO2810

Inox AISI 304 - UNI EN 10088

Inox AISI 316L - UNI EN 10088

Sistema Certificato

- IMQ
- EN 61537-1 ed.2007
- EN 50085-1:2005 ed EN 50085-2-1:2006
- UL file E471266

Attenzione: per materiale Serie ZT e ZM venduto/installato in USA e Canada, richiedere la marcatura UL