



Curva Salita 90° senza Coperchio



Disponibile nelle altezze (H):

50

75

100

Dimensione							Peso	Dati Tecnici		Codice
B							[Kg]	a	R	
75	01	03	11	15	40	41	0,63	205	100	T1 091 0707
100	01	03	11	15	40	41	0,70	205	100	T1 091 0710
150	01	03	11	15	40	41	0,83	205	100	T1 091 0715
200	01	03	11	15	40	41	0,97	205	100	T1 091 0720
300	01	03	11	15	40	41	1,24	205	100	T1 091 0730
400	01	03	11	15	40	41	1,51	205	100	T1 091 0740
500	01	03	11	15	40	41	1,78	205	100	T1 091 0750
600	01	03	11	15	40	41	2,04	205	100	T1 091 0760

Spessori

Componente - 1,00mm

Certificazioni



E471266



Legenda Trattamenti

Zincato Sendzimir - UNI EN 10346

Zincatura a caldo per immersione - UNI EN ISO 1461

Grigio RAL 7032 - ISO9227-ISO6270-ISO2810

Blu RAL 5015 - ISO9227-ISO6270-ISO2810

Inox AISI 304 - UNI EN 10088

Inox AISI 316L - UNI EN 10088

Sistema Certificato

- IMQ
- EN 61537-1 ed.2007
- EN 50085-1:2005 ed EN 50085-2-1:2006
- UL file E471266

Attenzione: per materiale Serie ZT e ZM venduto/installato in USA e Canada, richiedere la marcatura UL