

Coperchio Discesa 30°

Disponibile nelle altezze (H):

50

75

100



Dimensione							Spessore	Peso	Dati Tecnici	Codice
B							[mm]	[Kg]	R	
50	01	03	11	15	40	41	0,80	0,07	100	T1 102 0505
100	01	03	11	15	40	41	0,80	0,11	100	T1 102 0510
150	01	03	11	15	40	41	0,80	0,15	100	T1 102 0515
200	01	03	11	15	40	41	0,80	0,20	100	T1 102 0520
300	01	03	11	15	40	41	0,80	0,28	100	T1 102 0530
400	01	03	11	15	40	41	0,80	0,37	100	T1 102 0540
500	01	03	11	15	40	41	0,80	0,46	100	T1 102 0550
600	01	03	11	15	40	41	0,80	0,55	100	T1 102 0560

Certificazioni



E471266



Legenda Trattamenti

 Zincato Sendzimir - UNI EN 10346

 Zincatura a caldo per immersione - UNI EN ISO 1461

 Grigio RAL 7032 - ISO9227-ISO6270-ISO2810

 Blu RAL 5015 - ISO9227-ISO6270-ISO2810

 Inox AISI 304 - UNI EN 10088

 Inox AISI 316L - UNI EN 10088

Sistema Certificato

- IMQ
- EN 61537-1 ed.2007
- EN 50085-1:2005 ed EN 50085-2-1:2006
- UL file E471266
- Attenzione: per materiale Serie ZT e ZM venduto/installato in USA e Canada, richiedere la marcatura UL