


Raccordo Piano a T senza Coperchio



Disponibile nelle altezze (H):

50

75

100

Dimensione						Peso	Dati Tecnici			Codice
B						[Kg]	a	b	R	
100	01	03	11	15	40	41	1,16	230	360	100 T1 105 1010
150	01	03	11	15	40	41	1,45	280	410	100 T1 105 1015
200	01	03	11	15	40	41	1,79	330	460	100 T1 105 1020
300	01	03	11	15	40	41	2,57	430	560	100 T1 105 1030
400	01	03	11	15	40	41	3,51	530	660	100 T1 105 1040
500	01	03	11	15	40	41	4,61	630	760	100 T1 105 1050
600	01	03	11	15	40	41	5,86	730	860	100 T1 105 1060

Spessori

Componente - 1,00mm

Certificazioni



E471266



Legenda Trattamenti

Zincato Sendzimir - UNI EN 10346

Zincatura a caldo per immersione - UNI EN ISO 1461

Grigio RAL 7032 - ISO9227-ISO6270-ISO2810

Blu RAL 5015 - ISO9227-ISO6270-ISO2810

Inox AISI 304 - UNI EN 10088

Inox AISI 316L - UNI EN 10088

Sistema Certificato

- IMQ
- EN 61537-1 ed.2007
- EN 50085-1:2005 ed EN 50085-2-1:2006
- UL file E471266

Attenzione: per materiale Serie ZT e ZM venduto/installato in USA e Canada, richiedere la marcatura UL