


Raccordo a Croce senza Coperchio



Disponibile nelle altezze (H):

50

75

100

Dimensione							Peso	Dati Tecnici			Codice
B							[Kg]	a	R		
75	01	03	11	15	40	41	1,10	335	100	T1 111 0707	
100	01	03	11	15	40	41	1,24	360	100	T1 111 0710	
150	01	03	11	15	40	41	1,54	410	100	T1 111 0715	
200	01	03	11	15	40	41	1,88	460	100	T1 111 0720	
300	01	03	11	15	40	41	2,68	560	100	T1 111 0730	
400	01	03	11	15	40	41	3,64	660	100	T1 111 0740	
500	01	03	11	15	40	41	4,75	760	100	T1 111 0750	
600	01	03	11	15	40	41	6,03	860	100	T1 111 0760	

Spessori

Componente - 1,00mm

Certificazioni



E471266



Legenda Trattamenti

Zincato Sendzimir - UNI EN 10346

Zincatura a caldo per immersione - UNI EN ISO 1461

Grigio RAL 7032 - ISO9227-ISO6270-ISO2810

Blu RAL 5015 - ISO9227-ISO6270-ISO2810

Inox AISI 304 - UNI EN 10088

Inox AISI 316L - UNI EN 10088

Sistema Certificato

- IMQ
- EN 61537-1 ed.2007
- EN 50085-1:2005 ed EN 50085-2-1:2006
- UL file E471266

Attenzione: per materiale Serie ZT e ZM venduto/installato in USA e Canada, richiedere la marcatura UL